



ソダテック 400W High-Pressure Sodium Lamps スペックシート



Lamp Type: Super High-Pressure Sodium Lamps (American National Standard)

Control Gear: S51 or **Electronic Ballast**

| Performance Data | |
|--------------------------------------|-----------|
| Light Output (Lumens @ 100 hours) | 55000 |
| Lamp Lumens Per Watt | 132 |
| Rated Life (Hrs. @ 10 Hr. /Start) | 24000 |
| Correlated Colour Temperature (K) | 2000K |
| Colour Rendering Index (CRI) or (Ra) | 20 |
| Starting time. Max (s) | 5 |
| Burning Position | Universal |

| Physical Data / Requirements | |
|-------------------------------------|----------|
| Base Designation | E39 |
| Bulb Designation | T15 |
| Bulb Diameter (mm) | 48 |
| Max. Overall Length (mm) | 285 |
| Light Centre Length (mm) | 175 |
| Max. Base Temperature (°C) | 210 |
| Max. Bulb Temperature (°C) | 430 |
| Luminaire Type | Enclosed |

| Lamp Electrical Data / Requirements | |
|--|-------|
| ANSI Standard | S51 |
| Lamp Wattage (W) | 420W |
| Lamp Operating Voltage (V) | 110V |
| Lamp Operating Current (Amps) | 4.3A |
| Min. Open Circuit Voltage (RMS) | 198 |
| Min. - Max. Starting Pulse (Peak KV) | 3-4.5 |
| Min. Pulse Width at 2250V (microseconds) | 1 |
| Min. Pulse Rate Per ½ cycle | 1 |
| Pulse Position (Electrical Degrees) | - |



Spectral Distribution

